DP89

Cemimax DP89 is Extremely high performance dispersion primer for absorbent subfloor.

ESPECIALLY SUITABIE FOR:

Use on surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

DESCRIPTION:

Dispersion Primer with a wide range of applications, for interior and exterior use, providing overlayment compound with all our levelling products is applied within drying time of primer. Not to be left exposed to the elements for more than 2 hours.

PRODUCT PROPERTIES:

- Ready to use.
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free.
- Suitable for exterior use

DP200

Cemimax DP200 is a pure polyurethane resin with very high quality developed particularly for subfloors that must be quickly brought to a condition ready for covering installation. Special can be used as low moisture vapor retarder for concrete and cement-based subfloors. For interior and exterior use.

ESPECIALLY SUITABIE FOR:

Use on substrates with low damp, on ceramic,terrazzo, stone subfloors, surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

PRODUCT PROPERTIES:

- Fast drying
- Increase the strength of the substrate
- Moisture barrier
- Excellent covering and filling capacity
- Solvent-free.

A350

Dispersion adhesive for resilient synthetic floor and wall coverings in interior areas.

ESPECIALLY SUITABIE FOR:

Rubber flooring sheet, PVC sport flooring sheet, vinyl tile and cushioned vinyl coverings, including those with textile fleece backings.

PRODUCT PROPERTIES:

- Good water resistance, excellent bonding strength.
- Very high initial tack and final bonding strength.
- Easy application, high coverage rate.
- Low VOC

A2000

Dispersion adhesive for resilient synthetic floor and wall coverings in interior areas.

ESPECIALLY SUITABIE FOR:

Rubber flooring sheet, PVC sport flooring sheet, vinyl tile and cushioned vinyl coverings, including those with textile fleece backings.

PRODUCT PROPERTIES:

- Stable quality Bonding, layer has durable resilience.
- Good water resistance, excellent bonding strength.
- Very high initial tack and final bonding strength.
- Easy application, high coverage rate.
- Low VOC

DT88

Cemimax DT88 is a polymer-modified, cement-based mortar for setting quarry, ceramic and most natural stone (including mosaics) and also for tiles over common interior surfaces, including exterior-grade plywood, as well as over exterior concrete and masonry surfaces. DT88 also can also be used to install porcelain tiles over common interior surfaces as well as exterior, horizontal concrete and masonry surfaces. DT88 is recommended for most tile sizes.

PRODUCT PROPERTIES/BENEFITS:

- Universal use for setting porcelain, quarry, ceramic and most tile floor coveringsnatural stone* tiles
- Water resistant
- Easy to mix and apply
- High bonding strength and long-term durability
- One-product Use for interior and exterior floors and walls

APPLICATION:

DT88 adheres to both dry and damp substrates that are structurally sound, solid and free from any contaminants. Plywood substrates must be dry. Wallboards must be dry, sound and securely anchored to structural components in the wall. Highly absorbent substrates, such as plaster, existing tiles and certain non-porous substrates must be primed or treated as detailed below before proceeding with the tile installation.

DP90

One component, low emission, multipurpose dispersion primer with carbon bre technology for non absorbency substrates

ESPECIALLY SUITABIE FOR:

- Use on non-absorbent substrates, very suitable for existing surfaces in need of refurbishment, such as well-bonded and non-water-solu-bleadhesive residues including cutback adhesive.
- Dense & smooth surfaces, on soundly bonded ceramic and natural stone tiles, terrazzo, water resistant coatings, epoxy coatings or metal surfaces.

DESCRIPTION:

Dispersion primer low emission, film forming primer for use over non-absorbent surfaces including non-water soluble adhesive residues. The product cannot be diluted with water and for interior and exterior use, providing overlayment compound DL10 or DL59 is applied within drying time of primer. Not to be left exposed to the elements for morethan 2 hours.

PRODUCT PROPERTIES:

- Ready to use
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free

A300

Cemimax A300 is a very low emission dispersion adhesive for almost all textile coverings, therefore truly universal strong thread-formation, giving reliable adhesion in interior areas.

ESPECIALLY SUITABIE FOR:

- Textile coverings with synthetic secondary backings
- Textile coverings with foam-, latex- or fleece- backings
- Woven goods, needlepunch and natural fibre carpets
- Felt-backed PVC and cushioned vinyl of thickness <2mm coverings

PRODUCT PROPERTIES:

- Stable quality Bonding, layer has durable resilience.
- Good water resistance, excellent bonding strength.
- Very high initial tack and final bonding strength.
- Easy application, high coverage rate.

ULTRAMAX MS

Ultramax MS is a one component high performance adhesive sealant based on Hybrid Silyl Modified Polymers. Ultramax Ms provides the strength of polyurethane with a weathering resistance and shorter cure times of silicone. The properties that Ultramax Ms is made up of is well suited as a adhesive sealant in the demanding building, construction and engineering industries which provides superb primerless adhesion to all Flooring materials commonly used in these industries. . This innovative and environmentally friendly product cures quickly in ambient temperatures and retains excellent bond strength, elasticity and tear resistance over the years. It skins over in a short time resisting dust and dirt pickup and can be applied in thick layers without shrinking or bubbling. Ultramax MS will not stain and is very compatible with commonly used flooring systems. It will not yellow or crack or show signs of aging when exposed to adverse weather conditions and harsh UV radiation. Ultramax Ms does not contain solvents, is ocyanates and silicones.

PRODUCT PROPERTIES:

- Fast curing
- No carcinogens
- Bulit in moisture barrier
- Acoustic properties
- Highly flexible
- Great beading stability
- Suitable for under floor heating
- Easy clean up

DT85

Cemimax DT85 is a cementitious polymer-modi-fied mortar adhesive providing excellent bond strength.
Suitable for the installation of most types of stone, porcelain and ceramic tiles.
For internal and external use.

PRODUCT PROPERTIES/BENEFITS:

- Universal use for installation of porcelain, quarry, ceramic and moisture sensitive stone.
- Easy to mix and apply.
- High bond strength and long term durability.
- One product for internal and external, walls and floors.
- Suitable to moisture sensitive stone.

APPLICATION:

DT85 adheres to both dry and damp substrates that are structurally sound, solid and free from any contaminants. Plywood substrates must be dry. Wallboards must be dry, sound and securely anchored to structural components in the wall. Highly absorbent substrates, such as plaster, existing tiles and certain non-porous substrates must be primed or treated as detailed below before proceeding with the tile installation.

DT Flextra 1

Cemimax DT Flextra 1 is a rubber-modified, cement- based adhesive with excellent high coverage ability.Designed for setting quarry, ceramic and most natural stone (including mosaics) and also for tiles over common interior surfaces, including exterior- grade plywood, as well as over exterior concrete and masonry surfaces. Cemimax DT Flextra 1 also can also be used to install porcelain tiles over common interior surfaces as well as exterior, horizontal concrete and masonry surfaces. DT Flextra 1 is recommended for most tile sizes.

PRODUCT PROPERTIES/BENEFITS:

- Excellent high coverage rate
- Universal use for setting porcelain, quarry, ceramic and most tile floor coveringsnatural stone* tiles
- Water resistant
- Easy to mix and apply
- High bonding strength and long-term durability
- One-product Use for interior and exterior floors and walls

APPLICATION:

DT Flextra 1 adheres to both dry and damp substrates that are structurally sound, solid and free from any contaminants. Plywood substrates must be dry. Wallboards must be dry, sound and securely anchored to structural components in the wall. Highly absorbent substrates, such as plaster, existing tiles and certain non-porous substrates must be primed or treated as detailed below before proceeding with the tile installation.

Cemimax

THE ULTIMATE IN FLOOR PREPARATION

DL33 CT C25-F6

DL33 is an advanced cement and polymer based levelling and smoothing compound. DL33 is formulated for leveling work on standard construction in universal areas. DL33 is suitable for internal use on new or existing substrates for trafficable areas that are used internally as a underlayment.

PRODUCT PROPERTIES/BENEFITS:

Plastic dry cement mortar with finely graded fillers. When mixed with water, produces a hydraulic-setting smoothing compound with good flow properties and high coverage.

COMPOSITION:

Special cements, mineral fillers, polyvinyl-acetate-copolymers, flow agents and additives.

- Easy apply
- Quick setting
- Superior flow – fast application
- Flexible – hand mix or pump application
- Very economic
- Interior use

DL55 CT C35-F8

DL55 is an advanced cement and polymer based levelling and smoothing compound. DL55 is formulated for experienced commercial contractors to smooth and level large commercial and retail areas. Once dry it is suitable for the application of vinyl, carpet and tile floor finishes. Unlike normal hydration levellers, DL55 will harden and dry at temperatures down to 10°C.

PRODUCT PROPERTIES/BENEFITS:

Plastic dry cement mortar with finely graded fillers. When mixed with water, produces a hydraulic-setting smoothing compound with good flow properties and high coverage.

COMPOSITION:

Special cements, mineral fillers, polyvinyl-acetate-copolymers, flow agents and additives.

- Super smooth - requires no sanding
- Versatile - apply 1.5mm to 40mm in one application
- Rapid hardening - walkable from 2 hours
- Superior flow - fast application
- Flexible - hand mix or pump application
- For Interior use
- Suitable for Radiant Floor Heating systems

DL59 CT C40-F8

DL59 is a cement based levelling compound with very high compressive strength to C40. DL59 is especially suitable for high traffic, heavy wear location. DL59 is especially used as overlays for polished concrete floors.

PRODUCT PROPERTIES/BENEFITS:

Plastic dry cement mortar with finely graded fillers. When mixed with water, produces a hydraulic-setting smoothing compound with good flow properties and high coverage.

COMPOSITION:

Special cements, mineral fillers, polyvinyl-acetate-copolymers, flow agents and additives.

- Extremely high flexible strength - 60%
- Versatile - apply 1.5mm to 40mm in one application
- Rapid hardening - walkable from 2 hours
- Flexible - hand mix or pump application
- Can be polished
- For Interior and Exterior use
- Suitable for Radiant Floor Heating systems
- Pigments can be added for colour
- Aggregates can be added for exposed stone effect

DL10 CT C30-F8

DL10 is an advanced cement and polymer-based levelling compound with special aggregate. DL10 is formulated with high flow performance for levelling work on the installation of thick layers. DL10 is very suitable for quick-setting preparation solutions and also can be used as a fast set screed with low ratio water mixing.

PRODUCT PROPERTIES/BENEFITS:

Plastic dry cement mortar with finely graded fillers. When mixed with water, produces a hydraulic-setting smoothing compound with good flow properties and high coverage.

COMPOSITION:

Special cements, mineral fillers, polyvinyl-acetate-copolymers, flow agents and additives.

- Easy application
- Quick setting
- Superior flow — fast application
- Can be used as a fast set screed
- High-depth limitation 1.5mm to 150mm
- Compatible with other cemimax levelling compounds
- For Interior and Exterior use
- Suitable for Radiant Floor Heating systems

BICOMAX CT C35-F6

Cemimax Bicomax is a Bi-Components high performance self leveling compound with low odour, fast setting, fast drying, special designed for wet areas , high moisture vapor control subfloor, exterior and suitable for preparing sound internal subfloors prior to the installation of new floorcoverings.

Bicomax is particularly suitable for use over old adhesive residues (including bitumen and carpet tile tackifiers) without the need for priming. Bicomax can be used for patch filling timber floors prior to overlaying with plywood. It is suitable for use in clinical and biologically sensitive areas such as hospitals, laboratories, clean rooms etc.
Bicomax mixed with set of Liquid component can be applied to suitably prepared steel decks in light to medium-duty traffic areas. Bicomax is unaffected by moisture and is suitable for application over damp, clean, uneven concrete and sand/cement screeds, prior to application of Cemimax waterproof surface membranes or direct application.

PRODUCT PROPERTIES/BENEFITS:

- Suitable for wet areas,high moisture vapor control , exterior
- Moisture tolerant - can be used under Cemimax waterproof surface membranes
- Can be filled up to 100mm
- Fast setting
- Excellent self-smoothing properties

DL59 FLEX

DL59 Flex is a Fiber-Reinforced cementitious self-leveling smoothing compound with enhanced flexural strength. It resists cracking and provides an exceptionally smooth, hard surface for use on timber substrate in residential and commercial areas.

COMPOSITION:

Special cements, mineral fillers, polyvinyl-acetate-copolymers, flow agents and additives.

- Fiber-reinforced, resists cracking or shrinking
- Super smooth – requires no sanding
- Extremely high strength of compressive and bending
- Versatile – apply 1.5mm to 100mm in one application
- Rapid hardening – walkable from 2 hours
- Superior flow – fast application
- Flexible – hand mix or pump application
- Can be polished
- For Interior and Exterior use
- Suitable for Radiant Floor Heating systems
- Suitable for use over acoustic underlays
- Pigments can be added for colour
- Aggregates can be added for exposed stone effect
- Suitable for timber flooring as direct stick and for overlayment over the timber substrate.

Cemi Screed

Cemimax Cemi Screed is a ready-to-use, eco-friendly, normal-setting and rapid-drying engineered screed.

COMPOSITION:

- Internal, external
- Ready-to-use, ensures constantlevels of performance
- Ideal in renovation work
- High dimensional stability and long-lasting performance
- High mechanical resistance for screeds subject to heavy traffic
- Suitable for laying ceramic tiles, porcelain tiles, natural stone, hardwood floors and resilient materials using adhesives。

PP3

PP3 is an advanced cement and polymer based patching compound for repair, filling and patching up to 13mm depth. Can be used on a variety of substrates prior to installation of most flooring products. Priming is not required for most applications.

PRODUCT PROPERTIES/BENEFITS:

Plastic dry cement mortar with finely graded fillers. When mixed with water, produces a hydraulic-setting smoothing compound.

COMPOSITION:

Special cements, mineral fillers, polyvinyl-acetate-copolymers, and additives.

- Fast dry formula
- High strength
- Very fine aggregates
- Variable water range
- Smooth surface finish
- Excellent absorbency
- Versatile product

PP5

PP5 is an advanced cement and polymer mix that highly versatile, rapid drying patching product. That mixes to smooth underlayment that eliminates subfloor issues prior to the installation of flooring. It's fine aggregates allows it to be installed from a feather edge up to high fill depth in one application. Superior bonding allows it to applied over concrete, existing well bonded flooring, properly prepared non-water soluble adhesive, and well bonded gypsum all without having to use primer in most applications. PP5 is a perfect solution for filling holes,crack repair, ramping, and embossing leveler. Interior and outdoor use.

PRODUCT PROPERTIES/BENEFITS:

- High depth limitation
- Fast Setting – within 15 minutes
- Superior Bonding - Eliminates the need for primer in most applications
- Low to No VOC - Healthy indoor air quality

DP70

Cemimax DP70 is a Low emission, multi-purpose dispersion primer for exterior use.

ESPECIALLY SUITABIE FOR:

Use on surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

DESCRIPTION:

Dispersion Primer with a wide range of applications, for interior and exterior use, providing overlayment compound with all our levelling products is applied within drying time of primer. Not to be left exposed to the elements for more than 2 hours.

PRODUCT PROPERTIES:

- Ready to use
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free
- Suitable for exterior use

DP80

One component, low emission, multipurpose dispersion primer with carbon bre technology for non absorbency substrates

ESPECIALLY SUITABLE FOR:

- Use on non-absorbent substrates, very suitable for existing surfaces in need of refurbishment, such as well-bonded and non-water-solubleadhesive residues including cutback adhesive.
- Dense & smooth surfaces, on soundly bonded ceramic and natural stone tiles, terrazzo, water resistant coatings, epoxy coatings or metal surfaces.

DESCRIPTION:

Dispersion primer low emission, film forming primer for use over non-absorbent surfaces including non-water soluble adhesive residues. The product cannot be diluted with water and for interior and exterior use, providing overlayment compound DL10 or DL59 is applied within drying time of primer. Not to be left exposed to the elements for morethan 2 hours.

PRODUCT PROPERTIES:

- Ready to use
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free

Cemimax Australia Pty Ltd
Sydney Office and Warehouse:
5 Coates Place, Wetherill Park NSW 2164
Melbourne Warehouse:
21 Pauljoseph Way, Truganina VIC 3029
Brisbane Warehouse:
Unit 8 130 Kingston Road, Underwood, QLD 4119
Phone number: 02 8711 9778
Orders@cemimaxaustralia.com
www.cemimaxaustralia.com

New Zealand Office and Warehouse:
236C Bush Road, Rosedale, Auckland 0632
Phone number: 021 023 13450
info@cemimax.co.nz