

# CEMIMAX A2000

## Semi-pressure sensitive universal adhesive for all common floor covering types

### Description:

A2000 is a strong dispersion adhesive .It provides a short open and long working time for application with tnepressure sensitive, wet set adhesive and double drop bonding method. For use on floors and walls. For interior use.

### Especially suitable for:

- for homogeneous and heterogeneous PVC floor coverings in sheets and tiles
- for rubber floor coverings in sheets up to 4 mm (e.g.noraplan®) and floor coverings with acoustic or foam underlay
- for textile floor coverings with all common backings
- for light needle punch or woven carpet
- for PVC design floor coverings
- for linoleum in sheets up to 3,2 mm
- on warm water underfloor heating system

### Product Properties:

- Stable quality Bonding, layer has durable resilience.
- Good water resistance, excellent bonding strength.
- Very high initial tack and final bonding strength.
- Easy application, high coverage rate.
- Low VOC

### Binders:

Modified polyacrylate-copolymers with bond strengthening resins.

### Technical Data: ( Under normal conditions at 20°C.)

**Packaging:** 5kg,25kg Plastic drum

**Shelf-life:** Min. 12 months

**Colour:** Cream-white

**Working temperature:** +5°C - 35°C

**Consumption:** 3.75m<sup>2</sup>/1 Litres

**Open time:** 5-30 minutes

**Working time:** 1-2 hours

**Set to traffic:** After 24-48 hours

**Final strength:** After 5-7 days

### Substrate Preparation:

The subfloor must be sound, load bearing, level, dry, free from cracks, clean and free from material which would impair adhesion (e.g. dirt, oil, grease). The surface must be vacuumed, primed and levelled thoroughly.

### Application:

- Allow primers and smoothing compounds to dry thoroughly. Refer to the product Data Sheet for the products used.
- Stir thoroughly the product before use, Apply it evenly on the surface of substrate by using A2 or A3 toothed trowel. After short open time of 5-30 min. the substrate is ready to accept above flooring material.
- After the flooring material is applied on the substrate rub the surface by wood plate or roll by roller to remove entranced air under the flooring material. Make sure that the adhesive has transferred to the back of the flooring material.
- The adhesive will be dried after 24h, and set to foot traffic after 48h.

### Notes:

The product should be protected against frost and direct light during transportation, storage and application. Application temperature should not be lower than 5°C.

