

# CEMIMAX DP30

**Cemimax DP30 is a Low emission, multi-purpose dispersion primer for existing surfaces.**

## Description:

DP 30 is a solvent free, acrylic primer concentrate for use on absorbent substrates prior to the installation of Cemimax cement-based patches and levelers. DP 30 can be used over sound, properly bonded wood subfloors, gypsum, and non-water soluble adhesive residue over concrete.

## Especially suitable for:

Use on surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

## Product Properties:

- Ready to use.
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free.

## Binders:

Modified styrene-acrylate copolymers, wetting- and defoaming-agents, preservatives and water.

## Technical Data: ( Under normal conditions at 20°C.)

**Packaging:** Plastic bucket

**Packsize:** 20 kg, 5 kg

**Shelf-life:** 12 months

**Working temperature:** +5°C - 35°C

**Consumption:** Approx. 12m<sup>2</sup>/1 Litre

**Drying time:** 4-6 hours

**Touch Dry:** 15-20mins

- Drying times: allow to dry to a clear, transparent, almost tack-free film. Dependant upon floor temperature and humidity, In favourable climatic conditions and on absorbent surfaces, a drying time of 1-3 hours is normally adequate.

## Notes:

The product should be protected against frost and direct light during transportation, storage and application. Application temperature should not be lower than 5°C.

## Application:

- The surface should be clean, dry, and strong without loose layer should be completely removed by granulator, and the substrate should be cleaned thoroughly.
- The product can be diluted with water. The water proportion base on the substrate situation.(note: if the existing substrate is ceramic tile, it shall not be diluted.)
- Apply the primer evenly to fully cover the surface using a fine-pored foam roller.

