

CEMIMAX DP89

Cemimax DP89 is Extremely high performance dispersion primer for absorbent subfloor.

Description:

Dispersion Primer with a wide range of applications, for interior and exterior use, providing overlayment compound with all our levelling products is applied within drying time of primer. Not to be left exposed to the elements for more than 2 hours.

Especially suitable for:

Use on surfaces with well-bonded, waterproof adhesive and smoothing compound residues.

Product Properties:

- Ready to use.
- Excellent bond
- Rapid drying
- High coverage
- Solvent-free.
- Suitable for exterior use

Binders:

Modified styrene-acrylate copolymers, wetting- and defoaming-agents, preservatives and water.

Technical Data: (Under normal conditions at 20°C.)

Packaging: Plastic bucket

Packsize: 20 kg, 5 kg

Shelf-life: 12 months

Working temperature: +5°C - 35°C

Consumption: Approx. 12m²/1 Litre

Drying time: 4-6 hours

Touch Dry: 15-20mins

Application:

- The surface should be sound and clean, also dried without any loose particles or contamination. Any debris should be completely removed by vacuum or thorough cleaning leaving the substrate ready for use.
- The product need to be diluted with water 1:1 . The water proportion is based on the substrate situation.
- Apply the primer evenly to fully cover the surface using a fine-pored foam roller.

- Drying times: allow to dry to a clear, transparent, almost tack-free film. Dependant upon floor temperature and humidity, In favourable climatic conditions and on absorbent surfaces, a drying time of 1-3 hours is normally adequate.

Notes:

The product should be protected against frost and direct light during transportation, storage and application. Application temperature should not be lower than 5°C.

